



#### 1.MATERIAL :

1.1 INSULATOR : PA46.UL94V-0  
INSULATOR COLOR : BLACK

1.2 CONTACT : BRASS

2. FINSH :

2.1 CONTACT : 100u" Min.TIN PLATED INOVER  
50u" Min.NICKEL UNDERPLATED OVERLL.

#### 3. ELECTRICAC CHARACTERISTICS

3.1 CURRENT RATING: 3.0A

3.2 CONTACT RESISTANCE:30mΩ MAX.

3.3 INSULATION RESISTANCE :10000Ω MIN DC500V.

3.4 DIELECTRIC WITHSTANDING VOLATGE: AC 500V PER MINUTE.

3.5 OPERATING TEMPERATURE: -10° C ~ +85° C.

#### 4.NOTES:

4.1 THIC COMPONENT NAD ITS HOMOGENEOUS.  
SUBCOMPONENTS ARE RoHS COMPLIANT.

4.2 RESISTANCE TO SOLDERINC HEAT: 245°C±5°C FOR 5 SECONDS.

AND ONLY FOR WAVE SOLDERING PROCESS.

QUALITY SYMBOLS <div>▽ II 0</div>	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRAWN BY DATE Angel 2019/07/22		<div>CONSHARE</div>		
			CHECKED BY DATE Paul 2019/07/22				
			APPROVED BY DATE Paul 2019/07/22		TITLE 2.54mm筒牛-2*4P 公头塑胶		
					P/N B701000140021		
				DRAWING NO. B701000140021			
				SHEET NO. 1 OF 1			
ANGULAR± 2		FRAME SIZE		A1	SCALE 1:1	DESIGN UNITS MM	<div><div></div><div></div></div> THIRD ANGLE PROJECTION