

RECOMMENDED PCB LAYOUT
TOLERANCE ±0.05

NOTES:

1. MATERIAL:

HOUSING: SOLDER REFLOW PROCESS COMPATIBLE LCP,BLACK,UL 94V-0
CONTACTS: HIGH PERFORMANCE COPPER ALLOY, PLATING REFER TO P/N
SYSTEM
LATCH: STAINLESS STEEL, SOLDERABLE NICKEL OVERALL

2. RoHS COMPLIANT

The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements


3. P/N ORDER

SLIMSAS SERIAL A 8 6 W 1 0 2 7 4 A S F 2
2: PLPELINED CODE
PDUUCT PITCH
1: 100mm pitch #1 Type;
6: 0.60mm pitch #1 Type;
H-HOUSE
W-ASSEMBLY PRODUCT
0: 180° 1: 90°
F: WITH LOCATING POST
S: SMT TYPE
HSG COLOR: A: BLACK
CONTACT NUMBER:
74 : 74PIN CONTACT
2 : DOUBLE ROW CONTACT
3 :THREE ROW CONTACT
D: UL94V-0;
1:UL94V-1;

一般公差 GENERAL TOLERANCE

X. X ±0.30	X° ±5°
X. XX ±0.25	X. X° ±2°
X. XXX ±0.05	▲ MAJOR DIM.

单位 UNIT
mm



CUSTOMER DRAWING

绘图 DR.	
审核 CHK.	
核准 APPD.	KEVIN L



品名 TITLE:

SLIMSAS X8_SOCKET R/A

料号 PART NO.: A86W10274ASF2

文件编号 NUMBER: ENDE05

比例 SCALE SHEET 版次 REV.

1/1 1/1 A